



LUBRICATE ALL SEALS WITH CLEAN HYDRAULIC OIL PRIOR TO ASSEMBLY. DO NOT USE SILICONE BASED LUBRICANTS.



No.	QTY	PART No.	DESCRIPTION	Std. Seal Kit	FKM Seal Kit
N/A	N/A	6V150218	SEAL KIT, FKM		NOTED
N/A	N/A	60150227	SEAL KIT, STANDARD	NOTED	
11	1	39T55004	GASKET, (-134)	X	X
10	1	39H11056	SEAL, T, (1 9/16X5/32X1 3/4)	X	39V11056
9	1	81531804	RETAINER, SC, DA, PORTED		
8	1	81511800	PLUNGER, SC, 5000#		
7	1	39011061	WIPER, SNAP-IN, (1-1/4)	X	39053005
6	1	39011060	SEAL, BEVEL W/HEEL INSERT, 1-1/4 x1/8 x1-1/2	X	39052015
5	1	39000038	O-RING, (-008)	X	39051021
4	1	30601144	PLUG, SOCH, SAE 4		
3	1	30601130	ASSY, PLUG, SOCH, SAE 3, 303 SSTL		
2	1	23600013	BALL STEEL, ALLOY, 312	X	X
1	1	21410022	BHCS, 5/8-18 x 1, ALY		

**PARTS LIST**



VEKTEK, INC.  
1334 E. SIXTH AVE. P.O. BOX 625  
EMPORIA, KS. 66801 U.S.A.

( WEIGHT 7.51 LBS )

N	4395	RELEASE	JDW	03/18/21
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	JACOB	<b>DRAWING STATUS: Released</b>		
DATE:	03/26/92	PRODUCTION APPROVED FOR RELEASED STATUS ONLY		

ASSEMBLIES AFFECTED  
15021802  
15021802F

PARTS LIST, ASSY, SC, TB, 5000, DA, BP	
SIZE A	PL1541
REV N	

FORM FEG035\_PL\_ASIZE, REV. B

SHEET 1 OF 1