



LUBRICATE ALL SEALS WITH CLEAN HYDRAULIC OIL PRIOR TO ASSEMBLY. DO NOT USE SILICONE BASED LUBRICANTS.




TIGHTEN TO 55 FT-LBS TORQUE  
USE VEKTEK TORQUE TOOL  
NEW STYLE TORQUE TOOL AT200151, 10 POINTED TOOL (CIRCA 2018)  
OLD STYLE TORQUE TOOL AT200150, 2 POINTED SPANNER HOLE TOOL

INSTALL LIPS DOWN




T-SEAL  
INSTALLATION INFO

3 piece seal  
Assemble with T-seal  
between backup rings.



T-seal



Backup-ring

BODY,  
NOT A REPLACEMENT PART

N/A	N/A	6V200214	SEAL KIT, FKM		NOTED
N/A	N/A	60200215	SEAL KIT, STANDARD		NOTED
6	1	39H11031	SEAL, T, (1 5/16X5/32X1 1/2)	X	39V11031
5	1	82031501	GLAND, CYL, 8800 & 39.9 KN		
4	1	82011506	PISTON, CYL, 8800, 2 STRK		
3	1	39011048	SEAL, LL, (1-1/8 X 1/8 X 1/8 X 1-3/8)	X	39012007
2	1	39011019	WIPER, SNAP-IN, (1-1/8)	X	39050020
1	1	39001013	O-RING, (-029)	X	39012014
No.	QTY	PART No.	DESCRIPTION	Std. Seal Kit	FKM Seal Kit

### PARTS LIST



VEKTEK, INC.  
1334 E. SIXTH AVE. P.O. BOX 625  
EMPORIA, KS. 66801 U.S.A.

( WEIGHT 4.22 LBS )

G	4312	RELEASE	JDW	04/18/21
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	JACOB	<b>DRAWING STATUS: Released</b>		
DATE:	08/13/90	PRODUCTION APPROVED FOR RELEASED STATUS ONLY		

ASSEMBLIES AFFECTED  
20021502  
20021502F

PARTS LIST, ASSY, CYL, TB, DA, 2.0 STRK, 8800	
SIZE A	PL2060
REV G	

FORM FEG035\_PL\_ASIZE, REV. B

SHEET 1 OF 1