



Cavity Dimensions (mm)							
Model No.	G	B	C	D	E	Copper Gasket Torque (Nm)	Composite Gasket Torque (Nm)
42-1010-00*	M16x1,5	14,52±0,15	13,84±0.13	8	4	40	20
42-1010-01*	M20x1,5	18,52±0,15	16,81±0.13	9,5	4	54	30
42-1010-02*	M28x1,5	26,52±0,15	23,44±0.13	16	7	68	35
42-1010-03*							
42-1010-04	M35x1,5	33,52±0,15	31,19±0.13	22	7	N/A	50

*Both copper and composite gaskets are supplied. Either gasket may used, depending on the tightening requirements of the application.

INSTALLATION INSTRUCTIONS



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED

Cavity Dimensions

Cartridge Mounted Cylinders

-SEE CHART-

SIZE A 1SM2100

REV B

B	2583	RELEASE	K. ROEMER	10/30/13
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	JDW	DRAWING STATUS: Released		
DATE:	8-8-11	PRODUCTION APPROVED FOR RELEASED STATUS ONLY		