



Low Profile Swing Clamp Spacer Model No.	Top Flange Low Profile Swing Clamp Model No.	Top Flange Low Profile Clamp Capacity	A	B	C	D	E	F*	G*	H
64-0431-02	15-0521-XX	7500 LB	3.056	1.380	1.380	.713	1.630	1.750	1.750	.531
64-0431-02	15-0621-XX	7500 LB	3.056	1.380	1.380	.713	1.630	1.750	1.750	.531
64-0424-01	6951KN-22-XX	22 KN	2.492	1.080	1.080	.572	1.381	1.395	1.395	.422
64-0431-02	6951KN-33-XX	33 KN	3.056	1.380	1.380	.713	1.630	1.750	1.750	.531

* The numbers shown represent extrusion dimensions.

Note:
For proper sealing, mating surfaces should be flat within .003, with a maximum surface roughness of 63 μ m R_a

Instruction Sheet



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

C	1954	RELEASE	GLR	11/13/08
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY: M. Say	DRAWING STATUS: Released			
DATE: 11/16/2004	PRODUCTION APPROVED FOR RELEASED STATUS ONLY			

ASSEMBLIES AFFECTED

See Table

Low Profile Swing Clamp Spacer Machining Dimensions

SIZE	1S6402	REV	C
------	--------	-----	---

FORM FEG041-1S-ASIZE, REV. A

SHEET 1 OF 1