



1. APPLY LUBRICANT TO ALL SEALS DURING ASSEMBLY
DO NOT USE SILICONE BASED LUBRICANTS
2. INSTALL CARTRIDGE AND TORQUE TO 41 N-m
3. O-RING INCLUDED WITH P/N 70343760

NO	QTY	PART NO	DESCRIPTION	STD SEAL KIT
1	1	39000026	O-RING, (-906)	X
2	1	39000031	O-RING, (-012)	X
3	2	39050035	O-RING, (-017)	X
4	1	39050037	O-RING, (-015)	X
5	2	39054010	BU RING, (-012)	X
6	1	43068004	PLUG, SOCH, G1/8	
7	1	70343760	CHECK VALVE, CARTRIDGE	
8	1	87033103	PISTON, AB, PILOT CHK.	
9	1	87033106	PLUG, PO CHECK, SAE 6, METRIC	
10	1	39F54013	BU RING, (-015)	X
11	1	39F54014	BU RING, (-016)	X
12	1	39F54015	BU RING (-017)	X
N/A	N/A	60701200	KIT, SEAL, VLV, PO CHECK, CM	NOTED

PARTS LIST



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED
47033370

PARTS LIST, ASSY, PO CHECK, MM, METRIC

SIZE
A **MPL7177**

REV
B

SHEET 1 OF 1

FORM FEG035_PL.A.SIZE, REV. B

TORQUE TO 3 N-m

B	2748	RELEASE	DLG	9/22/14
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	DRAWING STATUS: Released			
DATE:	PRODUCTION APPROVED FOR RELEASED STATUS ONLY			