

4
1 USE VEKTEK AT200162 TO INSTALL

INSTALL WITH LIPS FACING BORE
USE VEKTEK AT200189 TO INSTALL

BODY NON-REPLACEMENT PART



2
2

6
1


3
2

1
1

7
2

5
1

TORQUE TO 7FT-LB
USE VEKTEK AT200175 TO INSTALL



LUBRICATE ALL SEALS WITH CLEAN HYDRAULIC OIL PRIOR TO ASSEMBLY
DO NOT USE SILICONE BASED LUBRICANTS

NO	QTY	PART NO	DESCRIPTION	STD SEAL KIT
1	1	23355011	SPRING, COMPRESSION	
2	2	30601122	PLUG, SOCH, SAE 2	
3	2	39052041	SEAL, U-CUP, 3/8 X 1/8 X 5/8	X
4	1	39053023	WIPER,PRESS-IN, (3/8)	X
5	1	82040010	CAP,CYL,BB,PULL,980LB	
6	1	82140001	PLUNGER,CYL,CM,PULL,980LB	
7	2	90199981	PIN,DOWEL,3/32 X 5/16,STD,SST,HDN	
N/A	N/A	60201117	KIT, SEAL, CYL, BB, PULL, 980LB	NOTED

PARTS LIST



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED
20-1106-01

PARTS LIST, ASSY,CYL,BB,PULL,980LB

8-32 PLNGER THD

SIZE
A PL2194

REV
A

SHEET 1 OF 1

A	3539	RELEASE	MJUST	7/18/18
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY:	MJUST	DRAWING STATUS: Released		
DATE:	3/15/18	PRODUCTION APPROVED FOR RELEASED STATUS ONLY		

FORM FEG035_PL_ASIZE, REV. B