

APPLY LUBRICANT TO ALL SEALS PRIOR TO INSTALLATION
DO NOT USE SILICONE TYPE LUBRICANTS.



NO	QTY	PART NO	DESCRIPTION	STD SEAL KIT
1	1	21440022	SHSS, CUP POINT	
2	1	23350015	SPRING, COMPRESSION	
3	1	31091006	FILTER, BRONZE, SINTERED, .250, 150µ	X
4	1	39000070	O-RING, (-904)	X
5	1	39050026	O-RING, (-018)	X
6	1	39050052	SEAL, PIN, STROKE, SWITCH, PRESS	X
7	1	39050053	O-RING, (-002)	X
8	1	39051075	O-RING, (24.5mm x 1.5)	X
9	1	39053003	WIPER,PRESS-IN, (1)	X
10	1	87075001	SHIM, ENDED, DOUBLE	
11	1	87075007	COLLAR, SWITCH, PRESSURE	
12	1	87075010	ADJUSTER, SWITCH, PRESSURE, SEVERE	
13	1	87075012	PLUNGER, CYL, PRESS, CONFIRMATION	
14	1	87075013	MOUNT, CYL, PRESS, CONFIRMATION	
15	1	87075014	PIN, STROKE, CYL, PRESS, CONFIRMATION	
16	1	39V53004	WIPER,PRESS-IN, (3/8), VBGV	X
N/A	N/A	62707004	KIT, SEAL, SWITCH, PRESS	NOTED

PARTS LIST



VEKTEK, INC.
1334 E. SIXTH AVE. P.O. BOX 625
EMPORIA, KS. 66801 U.S.A.

ASSEMBLIES AFFECTED
70-7500-79

SIZE
A PL7167

REV
B

FORM FEG035_PL_ASIZE, REV. B

MAIN BODY
(NOT A
REPLACEMENT PART)

B	5335	RELEASE	BDC	5/30/24
REV	IN ACCORDANCE WITH ECN	EFFECTIVE DATE	REVISED BY	DATE
DRW BY: DKC	DRAWING STATUS: DESIGN			
DATE: 7-13-11	PRODUCTION APPROVED FOR RELEASED STATUS ONLY			

SHEET 1 OF 1